This Business System has been produced by RAAS (UK) Ltd and must not be used in whole or in part without the express prior permission of © RAAS (UK) Ltd 2010



## ANNUAL EXCAVATOR SLI CHECK SHEET

MAKE/MODEL: CASE CX135	CX13S	DATE OF INSPECTION:	NEXT INSPECTION:	
ENGINEER: 3. FELL		SIGNATURE:		FLEET NO: 49
	Displayed Radius	Measured Radius	Known Weight Screen Weight	ASLI Function Pass/Fail
Max. Radius	6.52M	6.54M		PASS
Mid. Radius	S. Sam	S.63M		PASS
Min. RADIUS	4.28M	4.32M		PASS
LARGE WEIGHT			1980KG 1970KG	PASS
SMALL WEIGHT			1180KG 1150KG	PASS
SLEW LIMIT	LEFT:	MOTION CUT:	RIGHT:	MOTION CUT:
HEIGHT LIMIT	Воом:	DIPPER:	ARTIC BOOM:	MOTION CUT:
DATA LOGGER DOWNLOADED	YES (TICK)		DATA LOGGER RECORDING OK	YES (TICK)

## METHOD

- Set at maximum radius of machine taken from the duty charts and then tape from the centre of the slew ring to the centre of the lifting hook
- Record both the displayed radius and the actual taped measurement.
- 10 Repeat for the minimum chart radius plus a mid-point check and record as above. If radius checks okay, proceed with steps 5 – 8. IF NOT – DO NOT PROCEED but arrange corrective action.
  - Lift a known weight at the max. radius detailed in the charts for that weight
  - Repeat this using a small known weight.
  - Check the results are within the calibration as specified by PROLEC.
  - Check slew left and right for operation of limitation and motion cuts in both directions
  - Check excavator arm height limitation and motion cuts against machine acceptance certificate
- REPORT ANY FINDINGS WHICH REQUIRE FURTHER CLARIFICATION OR ATTENTION

Document Ref:	No of Pages:	Issue Date:	Issue No:
WBP-LAFT 01	Page 1 of 1	Oct 2016	4.1