


RATED LIFT CAPACITY CHART

Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom


Duty	Config	Sector	Osc Axle	Safety
1AU	ROAD	+/- 10° Over Osc End		75%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	6.85a	6.74b	6.02	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.35a	5.75a	5.05	4.25	3.61	-	-	-	-	-
5.00	-	-	-	3.95a	4.55a	5.10a	4.98	4.21	3.62	3.13	-	-	-	-
4.00	10.06a	0.57a	3.14a	4.54a	5.33a	5.72	4.78	4.08	3.53	3.08	2.70	-	-	-
3.00	-	-	-	0.79a	6.40	5.32	4.51	3.88	3.38	2.98	2.64	2.35	-	-
2.00	-	-	-	-	0.99a	4.92	4.23	3.68	3.23	2.87	2.56	2.30	-	-
1.00	-	-	-	-	1.57a	4.69	4.03	3.52	3.11	2.77	2.49	2.25	-	-
0.00	-	-	0.16a	1.72a	3.97a	4.60	3.93	3.43	3.03	2.71	2.45	-	-	-
-1.00	-	-	3.73a	5.18a	5.59	4.61	3.92	3.41	3.01	2.70	2.45	-	-	-
-2.00	-	-	7.81a	7.22	5.68	4.67	3.97	3.45	3.06	-	-	-	-	-
-3.00	-	-	-	-	-	4.36b	3.74b	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



Duty	Config	Sector	Osc Axle	Safety
1BU	ROAD	+/- 10° - +/- 45° Over Osc End		75%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	6.85a	6.30	4.82	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.35a	4.92	3.92	3.19	2.61	-	-	-	-	-
5.00	-	-	-	3.95a	4.55a	4.79	3.84	3.15	2.62	2.20	-	-	-	-
4.00	10.06a	0.57a	3.14a	4.54a	5.33a	4.48	3.62	3.00	2.52	2.15	1.83	-	-	-
3.00	-	-	-	0.79a	4.99	4.01	3.31	2.78	2.37	2.04	1.76	1.53	-	-
2.00	-	-	-	-	0.99a	3.56	2.99	2.55	2.20	1.92	1.68	1.47	-	-
1.00	-	-	-	-	1.57a	3.29	2.77	2.38	2.06	1.81	1.60	1.42	-	-
0.00	-	-	0.16a	1.72a	3.97a	3.19	2.66	2.28	1.98	1.75	1.55	-	-	-
-1.00	-	-	3.73a	5.18a	4.02	3.19	2.64	2.25	1.96	1.73	1.56	-	-	-
-2.00	-	-	7.81a	5.57	4.13	3.27	2.70	2.30	2.01	-	-	-	-	-
-3.00	-	-	-	-	-	3.45	2.87	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



NOTES	<p>SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).</p>
PAGE	1 of 18

RATED LIFT CAPACITY CHART


Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom

Duty	Config	Sector	Osc Axle	Safety
1CU	ROAD	+/- 45° - +/- 135°		75%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	6.85a	6.33	4.78	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.35a	4.88	3.86	3.11	2.54	-	-	-	-	-
5.00	-	-	-	3.95a	4.55a	4.75	3.77	3.07	2.55	2.12	-	-	-	-
4.00	10.06a	0.57a	3.14a	4.54a	5.33a	4.43	3.55	2.92	2.44	2.07	1.75	-	-	-
3.00	-	-	-	0.79a	4.95	3.94	3.23	2.69	2.28	1.95	1.68	1.45	-	-
2.00	-	-	-	-	0.99a	3.47	2.90	2.46	2.11	1.83	1.60	1.40	-	-
1.00	-	-	-	-	1.57a	3.19	2.67	2.28	1.97	1.72	1.52	1.34	-	-
0.00	-	-	0.16a	1.72a	3.89	3.09	2.56	2.18	1.89	1.66	1.47	-	-	-
-1.00	-	-	3.73a	5.18a	3.93	3.09	2.54	2.15	1.86	1.64	1.48	-	-	-
-2.00	-	-	7.81a	5.56	4.05	3.17	2.60	2.20	1.92	-	-	-	-	-
-3.00	-	-	-	-	-	3.36	2.77	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



Duty	Config	Sector	Osc Axle	Safety
1DU	ROAD	+/- 135° - +/- 160° Over Fixed End		75%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	6.85a	5.92	4.78	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.35a	4.85	4.03	3.39	2.87	-	-	-	-	-
5.00	-	-	-	3.95a	4.55a	4.75	3.96	3.35	2.87	2.48	-	-	-	-
4.00	10.06a	0.57a	3.14a	4.54a	5.33a	4.50	3.78	3.23	2.79	2.43	2.12	-	-	-
3.00	-	-	-	0.79a	4.90	4.12	3.52	3.04	2.65	2.33	2.06	1.82	-	-
2.00	-	-	-	-	0.99a	3.75	3.25	2.84	2.51	2.22	1.98	1.77	-	-
1.00	-	-	-	-	1.57a	3.53	3.06	2.69	2.39	2.13	1.92	1.73	-	-
0.00	-	-	0.16a	1.72a	3.97a	3.45	2.97	2.61	2.31	2.07	1.87	-	-	-
-1.00	-	-	3.73a	5.18a	4.15	3.45	2.96	2.59	2.29	2.06	1.88	-	-	-
-2.00	-	-	7.04	5.30	4.23	3.52	3.01	2.63	2.34	-	-	-	-	-
-3.00	-	-	-	-	-	3.66	3.15	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



NOTES	<p>SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).</p>
PAGE	2 of 18

RATED LIFT CAPACITY CHART

Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom

Duty	Config	Sector	Osc Axle	Safety
1EU	ROAD	+/- 160° - +/- 170° Over Fixed End		75%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	6.85a	6.74b	5.86	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.35a	5.75a	4.79	3.94	3.27	-	-	-	-	-
5.00	-	-	-	3.95a	4.55a	5.10a	4.71	3.90	3.28	2.79	-	-	-	-
4.00	10.06a	0.57a	3.14a	4.54a	5.33a	5.52	4.49	3.75	3.18	2.73	2.36	-	-	-
3.00	-	-	-	0.79a	6.27	5.05	4.18	3.53	3.03	2.62	2.29	2.01	-	-
2.00	-	-	-	-	0.99a	4.60	3.86	3.30	2.86	2.50	2.21	1.96	-	-
1.00	-	-	-	-	1.57a	4.33	3.64	3.13	2.72	2.40	2.13	1.91	-	-
0.00	-	-	0.16a	1.72a	3.97a	4.23	3.53	3.03	2.64	2.33	2.08	-	-	-
-1.00	-	-	3.73a	5.18a	5.31	4.23	3.51	3.00	2.62	2.32	2.09	-	-	-
-2.00	-	-	7.81a	7.26	5.42	4.31	3.57	3.05	2.67	-	-	-	-	-
-3.00	-	-	-	-	-	4.36b	3.74	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



Duty	Config	Sector	Osc Axle	Safety
1FU	ROAD	+/- 170° - +/- 180° Over Fixed End		75%

RADIUS

HEIGHT


	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	6.85a	6.74b	6.02	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.35a	5.75a	5.05	4.25	3.61	-	-	-	-	-
5.00	-	-	-	3.95a	4.55a	5.10a	4.98	4.21	3.62	3.13	-	-	-	-
4.00	10.06a	0.57a	3.14a	4.54a	5.33a	5.72	4.78	4.08	3.53	3.08	2.70	-	-	-
3.00	-	-	-	0.79a	6.40	5.32	4.51	3.88	3.38	2.98	2.64	2.35	-	-
2.00	-	-	-	-	0.99a	4.92	4.23	3.68	3.23	2.87	2.56	2.30	-	-
1.00	-	-	-	-	1.57a	4.69	4.03	3.52	3.11	2.77	2.49	2.25	-	-
0.00	-	-	0.16a	1.72a	3.97a	4.60	3.93	3.43	3.03	2.71	2.45	-	-	-
-1.00	-	-	3.73a	5.18a	5.59	4.61	3.92	3.41	3.01	2.70	2.45	-	-	-
-2.00	-	-	7.81a	7.22	5.68	4.67	3.97	3.45	3.06	-	-	-	-	-
-3.00	-	-	-	-	-	4.36b	3.74b	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



NOTES	<p>SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).</p>
PAGE	3 of 18

RATED LIFT CAPACITY CHART

Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom


Duty	Config	Sector	Osc Axle	Safety
1AL	ROAD	+/- 10° Over Osc End		75%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	6.85a	6.74b	6.43b	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.35a	5.75a	5.69	4.81	4.11	-	-	-	-	-
5.00	-	-	-	3.95a	4.55a	5.10a	5.59a	4.78	4.12	3.58	-	-	-	-
4.00	10.06a	0.57a	3.14a	4.54a	5.33a	5.86a	5.43	4.64	4.03	3.53	3.11	-	-	-
3.00	-	-	-	0.79a	7.30	6.07	5.15	4.44	3.88	3.43	3.05	2.72	-	-
2.00	-	-	-	-	0.99a	5.67	4.87	4.24	3.73	3.32	2.97	2.67	-	-
1.00	-	-	-	-	1.57a	5.44	4.67	4.08	3.61	3.22	2.90	2.62	-	-
0.00	-	-	0.16a	1.72a	3.97a	5.35	4.58	3.99	3.53	3.16	2.85	-	-	-
-1.00	-	-	3.73a	5.18a	6.49	5.36	4.56	3.97	3.51	3.15	2.86	-	-	-
-2.00	-	-	7.81a	8.34	6.58	5.42	4.61	4.01	3.56	-	-	-	-	-
-3.00	-	-	-	-	-	4.36b	3.74b	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



Duty	Config	Sector	Osc Axle	Safety
1BL	ROAD	+/- 10° - +/- 45° Over Osc End		75%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	6.85a	6.74b	6.43b	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.35a	5.75a	5.77b	4.82	4.05	-	-	-	-	-
5.00	-	-	-	3.95a	4.55a	5.10a	5.59a	4.78	4.06	3.48	-	-	-	-
4.00	10.06a	0.57a	3.14a	4.54a	5.33a	5.86a	5.51	4.63	3.96	3.42	2.98	-	-	-
3.00	-	-	-	0.79a	7.40a	6.27	5.20	4.41	3.80	3.31	2.92	2.58	-	-
2.00	-	-	-	-	0.99a	5.82	4.89	4.18	3.63	3.19	2.83	2.52	-	-
1.00	-	-	-	-	1.57a	5.55	4.66	4.01	3.50	3.09	2.75	2.47	-	-
0.00	-	-	0.16a	1.72a	3.97a	5.45	4.55	3.91	3.41	3.02	2.71	-	-	-
-1.00	-	-	3.73a	5.18a	6.82	5.45	4.54	3.88	3.39	3.01	2.71	-	-	-
-2.00	-	-	7.81a	8.51b	6.93	5.53	4.60	3.93	3.44	-	-	-	-	-
-3.00	-	-	-	-	-	4.36b	3.74b	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



NOTES	SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).
PAGE	4 of 18

RATED LIFT CAPACITY CHART


Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom

Duty	Config	Sector	Osc Axle	Safety
1CL	ROAD	+/- 45° - +/- 135°		75%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	6.85a	6.74b	6.43b	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.35a	5.75a	5.38	4.42	3.68	-	-	-	-	-
5.00	-	-	-	3.95a	4.55a	5.10a	5.30	4.38	3.69	3.14	-	-	-	-
4.00	10.06a	0.57a	3.14a	4.54a	5.33a	5.86a	5.07	4.23	3.59	3.08	2.67	-	-	-
3.00	-	-	-	0.79a	7.23	5.77	4.75	4.00	3.43	2.97	2.60	2.28	-	-
2.00	-	-	-	-	0.99a	5.30	4.42	3.77	3.26	2.85	2.51	2.23	-	-
1.00	-	-	-	-	1.57a	5.02	4.19	3.59	3.12	2.74	2.43	2.18	-	-
0.00	-	-	0.16a	1.72a	3.97a	4.92	4.08	3.48	3.03	2.67	2.39	-	-	-
-1.00	-	-	3.73a	5.18a	6.22	4.92	4.06	3.46	3.01	2.66	2.39	-	-	-
-2.00	-	-	7.81a	8.51b	6.34	5.00	4.12	3.51	3.06	-	-	-	-	-
-3.00	-	-	-	-	-	4.36b	3.74b	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



Duty	Config	Sector	Osc Axle	Safety
1DL	ROAD	+/- 135° - +/- 160° Over Fixed End		75%

RADIUS

HEIGHT


	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	6.85a	6.08	4.91	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.35a	4.99	4.14	3.49	2.96	-	-	-	-	-
5.00	-	-	-	3.95a	4.55a	4.89	4.07	3.46	2.97	2.56	-	-	-	-
4.00	10.06a	0.57a	3.14a	4.54a	5.33a	4.63	3.89	3.33	2.88	2.51	2.20	-	-	-
3.00	-	-	-	0.79a	5.06	4.25	3.63	3.14	2.74	2.41	2.14	1.89	-	-
2.00	-	-	-	-	0.99a	3.88	3.37	2.94	2.60	2.31	2.06	1.84	-	-
1.00	-	-	-	-	1.57a	3.67	3.18	2.79	2.48	2.21	1.99	1.80	-	-
0.00	-	-	0.16a	1.72a	3.97a	3.59	3.09	2.71	2.41	2.16	1.95	-	-	-
-1.00	-	-	3.73a	5.18a	4.31	3.59	3.07	2.69	2.39	2.14	1.96	-	-	-
-2.00	-	-	7.29	5.50	4.39	3.65	3.12	2.73	2.43	-	-	-	-	-
-3.00	-	-	-	-	-	3.80	3.26	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



NOTES	<p>SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).</p>
PAGE	5 of 18

RATED LIFT CAPACITY CHART

Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom


Duty	Config	Sector	Osc Axle	Safety
1EL	ROAD	+/- 160° - +/- 170° Over Fixed End		75%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	6.85a	6.74b	5.96	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.35a	5.75a	4.87	4.01	3.34	-	-	-	-	-
5.00	-	-	-	3.95a	4.55a	5.10a	4.79	3.97	3.35	2.85	-	-	-	-
4.00	10.06a	0.57a	3.14a	4.54a	5.33a	5.62	4.58	3.82	3.25	2.79	2.41	-	-	-
3.00	-	-	-	0.79a	6.40	5.15	4.26	3.60	3.09	2.68	2.35	2.06	-	-
2.00	-	-	-	-	0.99a	4.70	3.95	3.38	2.92	2.56	2.26	2.00	-	-
1.00	-	-	-	-	1.57a	4.43	3.73	3.20	2.79	2.46	2.18	1.95	-	-
0.00	-	-	0.16a	1.72a	3.97a	4.33	3.62	3.10	2.70	2.39	2.14	-	-	-
-1.00	-	-	3.73a	5.18a	5.43	4.33	3.60	3.08	2.68	2.38	2.14	-	-	-
-2.00	-	-	7.81a	7.42	5.54	4.41	3.66	3.12	2.73	-	-	-	-	-
-3.00	-	-	-	-	-	4.36b	3.74b	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-




Duty	Config	Sector	Osc Axle	Safety
1FL	ROAD	+/- 170° - +/- 180° Over Fixed End		75%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	6.85a	6.74b	6.43b	-	-	-	-	-	-	-	-
6.00	-	-	-	-	5.35a	5.75a	5.69	4.81	4.11	-	-	-	-	-
5.00	-	-	-	3.95a	4.55a	5.10a	5.59a	4.78	4.12	3.58	-	-	-	-
4.00	10.06a	0.57a	3.14a	4.54a	5.33a	5.86a	5.43	4.64	4.03	3.53	3.11	-	-	-
3.00	-	-	-	0.79a	7.30	6.07	5.15	4.44	3.88	3.43	3.05	2.72	-	-
2.00	-	-	-	-	0.99a	5.67	4.87	4.24	3.73	3.32	2.97	2.67	-	-
1.00	-	-	-	-	1.57a	5.44	4.67	4.08	3.61	3.22	2.90	2.62	-	-
0.00	-	-	0.16a	1.72a	3.97a	5.35	4.58	3.99	3.53	3.16	2.85	-	-	-
-1.00	-	-	3.73a	5.18a	6.49	5.36	4.56	3.97	3.51	3.15	2.86	-	-	-
-2.00	-	-	7.81a	8.34	6.58	5.42	4.61	4.01	3.56	-	-	-	-	-
-3.00	-	-	-	-	-	4.36b	3.74b	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



NOTES	<p>SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).</p>
PAGE	6 of 18

RATED LIFT CAPACITY CHART


Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom

Duty	Config	Sector	Osc Axle	Safety
2AU	RAIL	+/- 10° Over Osc End		67%
	 0mm - 50mm			

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.56b	6.25b	5.16	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.54a	5.22	4.31	3.62	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	5.10a	5.12	4.25	3.60	3.08	-	-	-	-
4.00	-	-	13.90b	6.38a	6.37a	6.01	4.90	4.10	3.49	3.02	2.63	-	-	-
3.00	-	-	-	1.98a	5.26a	5.56	4.60	3.89	3.34	2.91	2.56	2.26	-	-
2.00	-	-	-	-	0.86a	5.17	4.32	3.69	3.19	2.80	2.48	2.21	-	-
1.00	-	-	-	0.71a	1.98a	4.96	4.14	3.54	3.08	2.71	2.41	2.17	-	-
0.00	-	-	0.85a	2.42a	4.64a	4.89	4.06	3.46	3.01	2.66	2.38	-	-	-
-1.00	-	-	4.52a	6.04a	6.21	4.91	4.06	3.45	3.01	2.66	-	-	-	-
-2.00	-	-	-	7.87b	6.33	5.00	4.13	3.52	3.08	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-




Duty	Config	Sector	Osc Axle	Safety
2BU	RAIL	+/- 10° - +/- 45° Over Osc End		67%
	 0mm - 50mm			

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	5.00	3.76	2.91	-	-	-	-	-	-	-
6.00	-	-	-	-	5.02	3.79	2.98	2.39	1.93	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	3.64	2.87	2.32	1.91	1.58	-	-	-	-
4.00	-	-	9.01	5.90	4.29	3.31	2.65	2.17	1.81	1.52	1.28	-	-	-
3.00	-	-	-	1.98a	3.56	2.86	2.35	1.96	1.66	1.41	1.21	1.03	-	-
2.00	-	-	-	-	0.86a	2.47	2.07	1.76	1.51	1.30	1.13	0.98	-	-
1.00	-	-	-	0.71a	1.98a	2.26	1.89	1.61	1.39	1.21	1.06	0.94	-	-
0.00	-	-	0.85a	2.42a	2.78	2.19	1.81	1.54	1.33	1.16	1.03	-	-	-
-1.00	-	-	4.52a	3.92	2.83	2.21	1.81	1.53	1.32	1.16	-	-	-	-
-2.00	-	-	-	4.08	2.96	2.30	1.88	1.59	1.39	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



NOTES	SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).
PAGE	7 of 18

RATED LIFT CAPACITY CHART

Your safety, your profit, our commitment


Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom

Duty	Config	Sector	Osc Axle	Safety
2CU	RAIL	+/- 45° - +/- 135°		67%
	 0mm - 50mm			

RADIUS

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	6.66	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	3.80	2.97	2.36	-	-	-	-	-	-	-
6.00	-	-	-	-	3.82	3.00	2.41	1.97	1.61	-	-	-	-	-
5.00	-	-	-	3.85a	3.64	2.87	2.32	1.91	1.59	1.33	-	-	-	-
4.00	-	-	5.69	4.18	3.24	2.60	2.13	1.78	1.50	1.27	1.07	-	-	-
3.00	-	-	-	1.98a	2.65	2.22	1.88	1.59	1.36	1.17	1.01	0.87	-	-
2.00	-	-	-	-	0.86a	1.90	1.64	1.42	1.23	1.07	0.94	0.82	-	-
1.00	-	-	-	0.71a	1.98a	1.72	1.48	1.29	1.13	0.99	0.88	0.78	-	-
0.00	-	-	0.85a	2.42a	2.03	1.67	1.41	1.22	1.07	0.95	0.85	-	-	-
-1.00	-	-	3.79	2.69	2.07	1.68	1.41	1.21	1.07	0.95	-	-	-	-
-2.00	-	-	-	2.82	2.17	1.75	1.47	1.27	1.13	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-

HEIGHT




Duty	Config	Sector	Osc Axle	Safety
2DU	RAIL	+/- 135° - +/- 150° Over Fixed End		67%
	 0mm - 50mm			

RADIUS

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.56b	5.11	4.04	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.15	4.10	3.35	2.78	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	4.99	4.00	3.29	2.76	2.33	-	-	-	-
4.00	-	-	12.39	6.38a	5.98	4.66	3.78	3.14	2.65	2.27	1.95	-	-	-
3.00	-	-	-	1.98a	5.25	4.22	3.48	2.93	2.50	2.16	1.88	1.65	-	-
2.00	-	-	-	-	0.86a	3.82	3.20	2.72	2.35	2.05	1.81	1.60	-	-
1.00	-	-	-	0.71a	1.98a	3.61	3.02	2.58	2.24	1.96	1.74	1.55	-	-
0.00	-	-	0.85a	2.42a	4.47	3.55	2.94	2.50	2.17	1.91	1.71	-	-	-
-1.00	-	-	4.52a	6.04a	4.52	3.56	2.94	2.49	2.17	1.92	-	-	-	-
-2.00	-	-	-	6.33	4.64	3.65	3.01	2.56	2.23	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-

HEIGHT





NOTES	SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).
PAGE	8 of 18



Your safety, your profit, our commitment

RATED LIFT CAPACITY CHART


Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom



Duty	Config	Sector	Osc Axle	Safety
2EU	RAIL  0mm - 50mm	+/- 150° - +/- 160° Over Fixed End		67%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.56b	6.25b	5.63	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.54a	5.69	4.72	3.97	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	5.10a	5.59	4.65	3.95	3.39	-	-	-	-
4.00	-	-	13.90b	6.38a	6.37a	6.53a	5.37	4.50	3.84	3.33	2.91	-	-	-
3.00	-	-	-	1.98a	5.26a	6.12	5.07	4.29	3.69	3.22	2.84	2.51	-	-
2.00	-	-	-	-	0.86a	5.73	4.79	4.09	3.55	3.11	2.76	2.46	-	-
1.00	-	-	-	0.71a	1.98a	5.52	4.61	3.94	3.43	3.02	2.69	2.42	-	-
0.00	-	-	0.85a	2.42a	4.64a	5.45	4.53	3.86	3.37	2.97	2.66	-	-	-
-1.00	-	-	4.52a	6.04a	6.91	5.47	4.52	3.86	3.36	2.98	-	-	-	-
-2.00	-	-	-	7.87b	7.03	5.56	4.60	3.92	3.43	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-




Duty	Config	Sector	Osc Axle	Safety
2FU	RAIL  0mm - 50mm	+/- 160° - +/- 180° Over Fixed End		67%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.56b	6.25b	5.63	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.54a	5.69	4.72	3.97	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	5.10a	5.59	4.65	3.95	3.39	-	-	-	-
4.00	-	-	13.90b	6.38a	6.37a	6.53a	5.37	4.50	3.84	3.33	2.91	-	-	-
3.00	-	-	-	1.98a	5.26a	6.12	5.07	4.29	3.69	3.22	2.84	2.51	-	-
2.00	-	-	-	-	0.86a	5.73	4.79	4.09	3.55	3.11	2.76	2.46	-	-
1.00	-	-	-	0.71a	1.98a	5.52	4.61	3.94	3.43	3.02	2.69	2.42	-	-
0.00	-	-	0.85a	2.42a	4.64a	5.45	4.53	3.86	3.37	2.97	2.66	-	-	-
-1.00	-	-	4.52a	6.04a	6.91	5.47	4.52	3.86	3.36	2.98	-	-	-	-
-2.00	-	-	-	7.87b	7.03	5.56	4.60	3.92	3.43	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-





NOTES	<p>SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).</p>
PAGE	9 of 18



Your safety, your profit, our commitment

RATED LIFT CAPACITY CHART


Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom



Duty	Config	Sector	Osc Axle	Safety
2AL	RAIL	+/- 10° Over Osc End		90%
	 0mm - 50mm			

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.56b	6.25b	6.07b	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.54a	5.77b	5.57b	5.43b	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	5.10a	5.60a	5.73b	5.46b	4.71	-	-	-	-
4.00	-	-	13.90b	6.38a	6.37a	6.53a	6.68a	6.22b	5.33	4.62	4.04	-	-	-
3.00	-	-	-	1.98a	5.26a	8.50	7.03	5.96	5.13	4.48	3.95	3.50	-	-
2.00	-	-	-	-	0.86a	7.06a	6.66	5.69	4.93	4.33	3.84	3.43	-	-
1.00	-	-	-	0.71a	1.98a	6.07a	6.42	5.49	4.78	4.21	3.76	3.38	-	-
0.00	-	-	0.85a	2.42a	4.64a	7.60	6.31	5.39	4.69	4.15	3.71	-	-	-
-1.00	-	-	4.52a	6.04a	8.68a	7.62	6.31	5.37	4.68	4.15	-	-	-	-
-2.00	-	-	-	7.87b	7.27b	6.59b	5.88b	5.15b	4.32b	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-




Duty	Config	Sector	Osc Axle	Safety
2BL	RAIL	+/- 10° - +/- 45° Over Osc End		90%
	 0mm - 50mm			

RADIUS

HEIGHT



	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.56b	6.18	5.13	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.54a	5.20	4.41	3.78	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	5.10a	5.09	4.35	3.76	3.27	-	-	-	-
4.00	-	-	11.04	6.38a	6.37a	5.72	4.85	4.18	3.64	3.19	2.82	-	-	-
3.00	-	-	-	1.98a	5.26a	5.27	4.54	3.95	3.47	3.08	2.74	2.44	-	-
2.00	-	-	-	-	0.86a	4.87	4.24	3.73	3.31	2.95	2.65	2.38	-	-
1.00	-	-	-	0.71a	1.98a	4.65	4.05	3.57	3.18	2.85	2.57	2.33	-	-
0.00	-	-	0.85a	2.42a	4.64a	4.58	3.96	3.48	3.10	2.79	2.53	-	-	-
-1.00	-	-	4.52a	6.04a	5.49	4.60	3.96	3.48	3.10	2.79	-	-	-	-
-2.00	-	-	-	6.95	5.61	4.69	4.04	3.54	3.17	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



NOTES	SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).
PAGE	10 of 18

RATED LIFT CAPACITY CHART


Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom



Duty	Config	Sector	Osc Axle	Safety
2CL	RAIL	$\pm 45^\circ - \pm 135^\circ$		90%
	 0mm - 50mm			

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.56b	6.02	4.80	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.54a	4.88	4.02	3.34	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	5.10a	4.75	3.94	3.31	2.81	-	-	-	-
4.00	-	-	13.12	6.38a	6.37a	5.47	4.47	3.74	3.18	2.72	2.35	-	-	-
3.00	-	-	-	1.98a	5.26a	4.91	4.10	3.48	2.99	2.59	2.26	1.98	-	-
2.00	-	-	-	-	0.86a	4.42	3.74	3.22	2.79	2.45	2.16	1.91	-	-
1.00	-	-	-	0.71a	1.98a	4.16	3.52	3.03	2.65	2.33	2.07	1.86	-	-
0.00	-	-	0.85a	2.42a	4.64a	4.07	3.42	2.93	2.56	2.27	2.03	-	-	-
-1.00	-	-	4.52a	6.04a	5.11	4.10	3.41	2.92	2.55	2.27	-	-	-	-
-2.00	-	-	-	6.97	5.26	4.21	3.50	3.00	2.64	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-




Duty	Config	Sector	Osc Axle	Safety
2DL	RAIL	$\pm 135^\circ - \pm 150^\circ$ Over Fixed End		90%
	 0mm - 50mm			

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.56b	6.25b	6.07b	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.54a	5.77b	5.57b	4.96	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	5.10a	5.60a	5.73	4.93	4.28	-	-	-	-
4.00	-	-	13.90b	6.38a	6.37a	6.53a	6.50	5.54	4.80	4.20	3.70	-	-	-
3.00	-	-	-	1.98a	5.26a	7.25	6.15	5.29	4.62	4.07	3.62	3.23	-	-
2.00	-	-	-	-	0.86a	6.80	5.81	5.05	4.44	3.94	3.52	3.17	-	-
1.00	-	-	-	0.71a	1.98a	6.07a	5.60	4.87	4.30	3.83	3.44	3.11	-	-
0.00	-	-	0.85a	2.42a	4.64a	6.48	5.50	4.78	4.22	3.77	3.40	-	-	-
-1.00	-	-	4.52a	6.04a	7.93	6.50	5.50	4.77	4.21	3.77	-	-	-	-
-2.00	-	-	-	7.87b	7.27b	6.59b	5.59	4.85	4.29	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



NOTES	SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).
PAGE	11 of 18

RATED LIFT CAPACITY CHART


Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom

Duty	Config	Sector	Osc Axle	Safety
2EL	RAIL	+/- 150° - +/- 160° Over Fixed End		90%
	 0mm - 50mm			

RADIUS

HEIGHT

	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00	8.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	9.91a	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	6.56b	6.25b	6.07b	-	-	-	-	-	-	-	-	-
6.00	-	-	5.11a	5.54a	5.77b	5.57b	5.43b	-	-	-	-	-	-	-
5.00	-	3.85a	4.51a	5.10a	5.60a	5.73b	5.46b	4.89	-	-	-	-	-	-
4.00	13.90b	6.38a	6.37a	6.53a	6.68a	6.22b	5.63	4.79	4.13	-	-	-	-	-
3.00	-	1.98a	5.26a	9.01b	7.74b	6.41	5.40	4.63	4.03	3.53	-	-	-	-
2.00	-	-	0.86a	7.06a	7.34	6.09	5.17	4.47	3.91	3.45	-	-	-	-
1.00	-	0.71a	1.98a	6.07a	7.04	5.86	4.99	4.33	3.81	3.39	-	-	-	-
0.00	0.85a	2.42a	4.64a	8.54a	6.91	5.74	4.89	4.26	3.76	-	-	-	-	-
-1.00	4.52a	6.04a	8.68a	8.40b	6.91	5.73	4.88	4.26	-	-	-	-	-	-
-2.00	-	7.87b	7.27b	6.59b	5.88b	5.15b	4.32b	-	-	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-




Duty	Config	Sector	Osc Axle	Safety
2FL	RAIL	+/- 160° - +/- 180° Over Fixed End		90%
	 0mm - 50mm			

RADIUS

HEIGHT

	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50	8.00	8.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	9.91a	-	-	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	6.56b	6.25b	6.07b	-	-	-	-	-	-	-	-	-
6.00	-	-	5.11a	5.54a	5.77b	5.57b	5.43b	-	-	-	-	-	-	-
5.00	-	3.85a	4.51a	5.10a	5.60a	5.73b	5.46b	4.89	-	-	-	-	-	-
4.00	13.90b	6.38a	6.37a	6.53a	6.68a	6.22b	5.63	4.79	4.13	-	-	-	-	-
3.00	-	1.98a	5.26a	9.01b	7.74b	6.41	5.40	4.63	4.03	3.53	-	-	-	-
2.00	-	-	0.86a	7.06a	7.34	6.09	5.17	4.47	3.91	3.45	-	-	-	-
1.00	-	0.71a	1.98a	6.07a	7.04	5.86	4.99	4.33	3.81	3.39	-	-	-	-
0.00	0.85a	2.42a	4.64a	8.54a	6.92	5.74	4.89	4.26	3.76	-	-	-	-	-
-1.00	4.52a	6.04a	8.68a	8.40b	6.91	5.73	4.88	4.26	-	-	-	-	-	-
-2.00	-	7.87b	7.27b	6.59b	5.88b	5.15b	4.32b	-	-	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-





NOTES	SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).
PAGE	12 of 18

RATED LIFT CAPACITY CHART

Your safety, your profit, our commitment


Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom



Duty	Config	Sector	Osc Axle	Safety
3AU	RAIL  50mm - 150mm	+/- 10° Over Osc End		67%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.55	5.00	3.95	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.04	4.01	3.27	2.71	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	4.88	3.91	3.21	2.69	2.27	-	-	-	-
4.00	-	-	12.11	6.38a	5.85	4.55	3.68	3.06	2.58	2.21	1.90	-	-	-
3.00	-	-	-	1.98a	5.11	4.11	3.39	2.85	2.43	2.10	1.83	1.60	-	-
2.00	-	-	-	-	0.86a	3.71	3.11	2.65	2.28	1.99	1.75	1.55	-	-
1.00	-	-	-	0.71a	1.98a	3.50	2.92	2.50	2.17	1.90	1.69	1.50	-	-
0.00	-	-	0.85a	2.42a	4.34	3.44	2.84	2.42	2.10	1.85	1.65	-	-	-
-1.00	-	-	4.52a	5.98	4.39	3.45	2.84	2.41	2.10	1.85	-	-	-	-
-2.00	-	-	-	6.15	4.51	3.54	2.91	2.48	2.16	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-




Duty	Config	Sector	Osc Axle	Safety
3BU	RAIL  50mm - 150mm	+/- 10° - +/- 45° Over Osc End		67%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	8.99	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	4.26	3.16	2.42	-	-	-	-	-	-	-
6.00	-	-	-	-	4.28	3.20	2.48	1.96	1.56	-	-	-	-	-
5.00	-	-	-	3.85a	4.05	3.05	2.38	1.90	1.54	1.25	-	-	-	-
4.00	-	-	7.53	4.91	3.55	2.72	2.15	1.75	1.43	1.19	0.98	-	-	-
3.00	-	-	-	1.98a	2.82	2.27	1.86	1.54	1.29	1.08	0.91	0.76	-	-
2.00	-	-	-	-	0.86a	1.88	1.58	1.33	1.14	0.97	0.83	0.71	-	-
1.00	-	-	-	0.71a	1.98a	1.67	1.39	1.19	1.02	0.88	0.77	0.67	-	-
0.00	-	-	0.85a	2.42a	2.04	1.60	1.31	1.11	0.96	0.83	0.73	-	-	-
-1.00	-	-	4.52a	2.93	2.09	1.62	1.31	1.10	0.95	0.83	-	-	-	-
-2.00	-	-	-	3.09	2.21	1.71	1.38	1.17	1.02	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-





NOTES	SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).
PAGE	13 of 18



Your safety, your profit, our commitment

RATED LIFT CAPACITY CHART


Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom



Duty	Config	Sector	Osc Axle	Safety
3CU	RAIL  50mm - 150mm	+/- 45° - +/- 135°		67%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	5.95	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	3.38	2.61	2.05	-	-	-	-	-	-	-
6.00	-	-	-	-	3.39	2.64	2.11	1.70	1.37	-	-	-	-	-
5.00	-	-	-	3.85a	3.22	2.52	2.02	1.65	1.35	1.11	-	-	-	-
4.00	-	-	4.98	3.65	2.81	2.24	1.83	1.51	1.26	1.05	0.88	-	-	-
3.00	-	-	-	1.98a	2.23	1.87	1.57	1.33	1.13	0.96	0.82	0.69	-	-
2.00	-	-	-	-	0.86a	1.54	1.33	1.15	1.00	0.86	0.74	0.64	-	-
1.00	-	-	-	0.71a	1.62	1.37	1.18	1.02	0.89	0.78	0.69	0.60	-	-
0.00	-	-	0.85a	2.10	1.61	1.31	1.11	0.96	0.84	0.74	0.65	-	-	-
-1.00	-	-	3.08	2.16	1.65	1.33	1.11	0.95	0.83	0.74	-	-	-	-
-2.00	-	-	-	2.29	1.74	1.40	1.17	1.00	0.89	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-




Duty	Config	Sector	Osc Axle	Safety
3DU	RAIL  50mm - 150mm	+/- 135° - +/- 150° Over Fixed End		67%

RADIUS

HEIGHT



	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	8.46	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	4.88	3.87	3.13	-	-	-	-	-	-	-
6.00	-	-	-	-	4.90	3.90	3.18	2.64	2.21	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	3.77	3.09	2.59	2.19	1.87	-	-	-	-
4.00	-	-	7.49	5.53	4.32	3.50	2.90	2.45	2.10	1.81	1.56	-	-	-
3.00	-	-	-	1.98a	3.73	3.12	2.65	2.27	1.96	1.71	1.50	1.32	-	-
2.00	-	-	-	-	0.86a	2.80	2.41	2.09	1.83	1.61	1.43	1.27	-	-
1.00	-	-	-	0.71a	1.98a	2.62	2.25	1.96	1.73	1.53	1.37	1.23	-	-
0.00	-	-	0.85a	2.42a	3.11	2.56	2.18	1.90	1.67	1.49	1.34	-	-	-
-1.00	-	-	4.52a	4.04	3.15	2.58	2.18	1.89	1.66	1.49	-	-	-	-
-2.00	-	-	-	4.17	3.25	2.65	2.24	1.94	1.73	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



NOTES	SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).
PAGE	14 of 18

RATED LIFT CAPACITY CHART


Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom



Duty	Config	Sector	Osc Axle	Safety
3EU	RAIL  50mm - 150mm	+/- 150° - +/- 160° Over Fixed End		67%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.56b	6.25b	5.21	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.54a	5.27	4.36	3.66	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	5.10a	5.17	4.30	3.64	3.11	-	-	-	-
4.00	-	-	13.90b	6.38a	6.37a	6.07	4.95	4.14	3.53	3.05	2.66	-	-	-
3.00	-	-	-	1.98a	5.26a	5.62	4.65	3.93	3.38	2.94	2.59	2.29	-	-
2.00	-	-	-	-	0.86a	5.23	4.37	3.73	3.23	2.83	2.51	2.24	-	-
1.00	-	-	-	0.71a	1.98a	5.02	4.19	3.58	3.12	2.75	2.44	2.19	-	-
0.00	-	-	0.85a	2.42a	4.64a	4.95	4.11	3.51	3.05	2.70	2.41	-	-	-
-1.00	-	-	4.52a	6.04a	6.28	4.97	4.11	3.50	3.04	2.70	-	-	-	-
-2.00	-	-	-	7.87b	6.40	5.06	4.18	3.56	3.11	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-




Duty	Config	Sector	Osc Axle	Safety
3FU	RAIL  50mm - 150mm	+/- 160° - +/- 180° Over Fixed End		67%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.56b	6.25b	5.82	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.54a	5.77b	5.07	4.43	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	5.10a	5.60a	5.02	4.41	3.91	-	-	-	-
4.00	-	-	12.10	6.38a	6.37a	6.53a	5.62	4.90	4.33	3.85	3.45	-	-	-
3.00	-	-	-	1.98a	5.26a	6.21	5.39	4.74	4.20	3.76	3.39	3.07	-	-
2.00	-	-	-	-	0.86a	5.93	5.18	4.57	4.08	3.67	3.33	3.03	-	-
1.00	-	-	-	0.71a	1.98a	5.77	5.04	4.46	3.99	3.60	3.27	2.99	-	-
0.00	-	-	0.85a	2.42a	4.64a	5.72	4.97	4.40	3.94	3.56	3.24	-	-	-
-1.00	-	-	4.52a	6.04a	6.77	5.73	4.97	4.39	3.93	3.56	-	-	-	-
-2.00	-	-	-	7.87b	6.85	5.80	5.03	4.44	3.98	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-





NOTES	SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).
PAGE	15 of 18



Your safety, your profit, our commitment

RATED LIFT CAPACITY CHART


Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom



Duty	Config	Sector	Osc Axle	Safety
3AL	RAIL	+/- 10° Over Osc End		90%
	 50mm - 150mm			

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.56b	6.25b	6.07b	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.54a	5.77b	5.57b	5.43b	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	5.10a	5.60a	5.73b	5.46b	5.03	-	-	-	-
4.00	-	-	13.90b	6.38a	6.37a	6.53a	6.68a	6.22b	5.57	4.96	4.44	-	-	-
3.00	-	-	-	1.98a	5.26a	8.01	6.94	6.10	5.41	4.84	4.36	3.94	-	-
2.00	-	-	-	-	0.86a	7.06a	6.66	5.88	5.25	4.72	4.27	3.89	-	-
1.00	-	-	-	0.71a	1.98a	6.07a	6.47	5.72	5.12	4.62	4.20	3.84	-	-
0.00	-	-	0.85a	2.42a	4.64a	7.35	6.39	5.64	5.05	4.56	4.16	-	-	-
-1.00	-	-	4.52a	6.04a	8.68a	7.36	6.38	5.63	5.04	4.56	-	-	-	-
-2.00	-	-	-	7.87b	7.27b	6.59b	5.88b	5.15b	4.32b	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-




Duty	Config	Sector	Osc Axle	Safety
3BL	RAIL	+/- 10° - +/- 45° Over Osc End		90%
	 50mm - 150mm			

RADIUS

HEIGHT



	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.56b	6.23	4.89	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.54a	4.98	4.05	3.33	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	5.10a	4.84	3.97	3.30	2.78	-	-	-	-
4.00	-	-	13.90b	6.38a	6.37a	5.63	4.54	3.76	3.16	2.69	2.31	-	-	-
3.00	-	-	-	1.98a	5.26a	5.03	4.14	3.48	2.96	2.55	2.21	1.92	-	-
2.00	-	-	-	-	0.86a	4.50	3.77	3.20	2.76	2.40	2.11	1.86	-	-
1.00	-	-	-	0.71a	1.98a	4.22	3.52	3.01	2.61	2.28	2.02	1.80	-	-
0.00	-	-	0.85a	2.42a	4.64a	4.13	3.41	2.91	2.52	2.22	1.97	-	-	-
-1.00	-	-	4.52a	6.04a	5.28	4.15	3.41	2.89	2.51	2.22	-	-	-	-
-2.00	-	-	-	7.44	5.44	4.27	3.51	2.98	2.60	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



NOTES	SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).
PAGE	16 of 18

RATED LIFT CAPACITY CHART


Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom



Duty	Config	Sector	Osc Axle	Safety
3CL	RAIL  50mm - 150mm	+/- 45° - +/- 135°		90%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.34	5.02	4.05	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.06	4.12	3.41	2.85	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	4.88	4.00	3.34	2.82	2.40	-	-	-	-
4.00	-	-	9.70	6.38a	5.59	4.52	3.74	3.16	2.70	2.32	2.00	-	-	-
3.00	-	-	-	1.98a	4.80	4.02	3.40	2.91	2.52	2.19	1.92	1.68	-	-
2.00	-	-	-	-	0.86a	3.58	3.08	2.67	2.34	2.06	1.82	1.61	-	-
1.00	-	-	-	0.71a	1.98a	3.34	2.87	2.50	2.20	1.95	1.74	1.56	-	-
0.00	-	-	0.85a	2.42a	3.96	3.27	2.78	2.41	2.13	1.89	1.70	-	-	-
-1.00	-	-	4.52a	5.16	4.02	3.28	2.78	2.40	2.12	1.89	-	-	-	-
-2.00	-	-	-	5.33	4.15	3.39	2.86	2.48	2.20	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-




Duty	Config	Sector	Osc Axle	Safety
3DL	RAIL  50mm - 150mm	+/- 135° - +/- 150° Over Fixed End		90%

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.56b	6.25b	6.07b	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.54a	5.77b	5.57b	4.69	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	5.10a	5.60a	5.51	4.66	3.98	-	-	-	-
4.00	-	-	13.90b	6.38a	6.37a	6.53a	6.34	5.30	4.52	3.90	3.39	-	-	-
3.00	-	-	-	1.98a	5.26a	7.19	5.94	5.02	4.32	3.76	3.30	2.91	-	-
2.00	-	-	-	-	0.86a	6.66	5.57	4.75	4.12	3.61	3.19	2.84	-	-
1.00	-	-	-	0.71a	1.98a	6.07a	5.32	4.55	3.96	3.49	3.10	2.78	-	-
0.00	-	-	0.85a	2.42a	4.64a	6.29	5.22	4.45	3.87	3.42	3.06	-	-	-
-1.00	-	-	4.52a	6.04a	7.99	6.31	5.22	4.44	3.86	3.42	-	-	-	-
-2.00	-	-	-	7.87b	7.27b	6.43	5.31	4.52	3.96	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-





NOTES	<p>SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).</p>
PAGE	17 of 18



Your safety, your profit, our commitment

RATED LIFT CAPACITY CHART


Machine Type	Case 988	Equipment	4.30m + 2.10m
Issue Date	11/08/2014	Serial No.	CGG0231310
System Type	PME RAIL	Additional Info.	Tool Pin, Monoboom



Duty	Config	Sector	Osc Axle	Safety
3EL	RAIL	+/- 150° - +/- 160° Over Fixed End		90%
	 50mm - 150mm			

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.56b	6.25b	6.07b	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.54a	5.77b	5.57b	5.43b	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	5.10a	5.60a	5.73b	5.46b	5.15	-	-	-	-
4.00	-	-	13.90b	6.38a	6.37a	6.53a	6.68a	6.22b	5.70	5.08	4.55	-	-	-
3.00	-	-	-	1.98a	5.26a	8.19	7.11	6.24	5.54	4.96	4.47	4.04	-	-
2.00	-	-	-	-	0.86a	7.06a	6.82	6.03	5.38	4.84	4.38	3.98	-	-
1.00	-	-	-	0.71a	1.98a	6.07a	6.63	5.87	5.25	4.74	4.30	3.94	-	-
0.00	-	-	0.85a	2.42a	4.64a	7.53	6.55	5.79	5.18	4.68	4.27	-	-	-
-1.00	-	-	4.52a	6.04a	8.68a	7.55	6.55	5.78	5.17	4.68	-	-	-	-
-2.00	-	-	-	7.87b	7.27b	6.59b	5.88b	5.15b	4.32b	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-




Duty	Config	Sector	Osc Axle	Safety
3FL	RAIL	+/- 160° - +/- 180° Over Fixed End		90%
	 50mm - 150mm			

RADIUS

HEIGHT

	1.00	1.50	2.00	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00	7.50
10.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
9.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
8.00	-	-	9.91a	-	-	-	-	-	-	-	-	-	-	-
7.00	-	-	-	-	6.56b	6.25b	6.07b	-	-	-	-	-	-	-
6.00	-	-	-	-	5.11a	5.54a	5.77b	5.57b	5.43b	-	-	-	-	-
5.00	-	-	-	3.85a	4.51a	5.10a	5.60a	5.73b	5.46b	5.24b	-	-	-	-
4.00	-	-	13.90b	6.38a	6.37a	6.53a	6.68a	6.22b	5.77b	5.22	4.68	-	-	-
3.00	-	-	-	1.98a	5.26a	8.43	7.31	6.42	5.70	5.11	4.60	4.17	-	-
2.00	-	-	-	-	0.86a	7.06a	7.02	6.21	5.54	4.98	4.51	4.11	-	-
1.00	-	-	-	0.71a	1.98a	6.07a	6.84	6.05	5.41	4.89	4.44	4.06	-	-
0.00	-	-	0.85a	2.42a	4.64a	7.77	6.75	5.97	5.34	4.83	4.40	-	-	-
-1.00	-	-	4.52a	6.04a	8.68a	7.78	6.75	5.96	5.33	4.83	-	-	-	-
-2.00	-	-	-	7.87b	7.27b	6.59b	5.88b	5.15b	4.32b	-	-	-	-	-
-3.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-4.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-
-5.00	-	-	-	-	-	-	-	-	-	-	-	-	-	-



NOTES	SWL = 75% of Tip Load or 87% of Max System Hydraulic Pressure (whichever is the lower). Radius/height are given in METRES. Loads are given in TONNES, and assume that the load is suspended vertically below the bucket pin with no other equipment attached. Loads marked 'b' boom and 'a' arm and 'r' artic are limited by hydraulic capacity (87% of system maximum hydraulic pressure).
PAGE	18 of 18