






**WILLIAM  
BRADSHAW**

**ANNUAL EXCAVATOR SLI CHECK SHEET**

MAKE/MODEL:	CASE 988.		DATE OF INSPECTION:	21/11/23		NEXT INSPECTION:	20/11/24.	
ENGINEER:	S. WATERS.		SIGNATURE:	<i>S. Waters</i>		FLEET NO:	36	
	Displayed Radius		Measured Radius		Known Weight	Screen Weight	ASLI Function Pass/Fail	
MAX. RADIUS	6.49m		6.48m				✓	
MID. RADIUS	5. m		5.02 m				✓	
MIN. RADIUS	3.6 m		3.57m				✓	
LARGE WEIGHT					1940kg	1978kg	✓	
SMALL WEIGHT					1180kg	1190kg	✓	
SLEW LIMIT	LEFT: 		MOTION CUT: <input checked="" type="checkbox"/>		RIGHT: 		MOTION CUT: <input checked="" type="checkbox"/>	
HEIGHT LIMIT	BOOM: 		DIPPER: 		ARTIC BOOM: 		MOTION CUT: <input checked="" type="checkbox"/>	
DATA LOGGER DOWNLOADED	YES (Tick)	<input checked="" type="checkbox"/>			DATA LOGGER RECORDING OK		YES (Tick)	<input checked="" type="checkbox"/>

**METHOD:**

1. Set at maximum radius of machine taken from the duty charts and then tape from the centre of the slew ring to the centre of the lifting hook.
2. Record both the displayed radius and the actual taped measurement.
3. Repeat for the minimum chart radius plus a mid-point check and record as above.
4. If radius checks okay, proceed with steps 5 – 8. **IF NOT – DO NOT PROCEED** but arrange corrective action.
5. Lift a known weight at the max. radius detailed in the charts for that weight.
6. Repeat this using a small known weight.
7. Check the results are within the calibration as specified by PROLEC.
8. Check slew left and right for operation of limitation and motion cuts in both directions.
9. Check excavator arm height limitation and motion cuts against machine acceptance certificate.
10. **REPORT ANY FINDINGS WHICH REQUIRE FURTHER CLARIFICATION OR ATTENTION**

Issue No:	4.1
Issue Date:	Oct 2016
No of Pages:	Page 1 of 1
Document Ref:	WBP- LAFT 01