This Business System has been produced by RAAS (UK) Ltd and must not be used in whole or in part without the express prior permission of © RAAS (UK) Ltd 2010



ANNUAL EXCAVATOR SLI CHECK SHEET

			NICH NO DO TON		
MAKE/MODEL: CASE 988	988	20/2/25	NEXT INSTECTION.	19/2/26	26.
ENGINEER: K. ANDIRES)K÷S	SIGNATURE: L. How	lives	п -	FLEET NO: 85
	Displayed Radius	Measured Radius	Known Weight Screen Weight		ASLI Function Pass/Fail
Max. Radius	7 M	6.9m			PASS
Mid. Radius	5-4m	5.2 m			Para
Min. Radius	3.84m	3.75m			P 1955
LARGE WEIGHT			1940 10	1920	520
SMALL WEIGHT			1180 11	1170,	CAES
SLEW LIMIT	LEFT:	MOTION CUT:	RIGHT:	-	MOTION CUT:
HEIGHT LIMIT	Воом:	DIPPER:	ARTIC BOOM:		MOTION CUT:
DATA LOGGER DOWNLOADED	YES (TICK)		DATA LOGGER RECORDING OK		YES (TICK)

- Set at maximum radius of machine taken from the duty charts and then tape from the centre of the slew ring to the centre of the lifting hook
- Record both the displayed radius and the actual taped measurement.
- Repeat for the minimum chart radius plus a mid-point check and record as above. If radius checks okay, proceed with steps 5 8. IF NOT DO NOT PROCEED but arrange corrective action.
- Lift a known weight at the max. radius detailed in the charts for that weight.
- Repeat this using a small known weight.
- 10 9 8 7 6 5 4 3 2 1 Check the results are within the calibration as specified by PROLEC.

 - Check slew left and right for operation of limitation and motion cuts in both directions.
 - Check excavator arm height limitation and motion cuts against machine acceptance certificate
- REPORT ANY FINDINGS WHICH REQUIRE FURTHER CLARIFICATION OR ATTENTION

Issue No: Issue Date:	4.1 Oct 2016 Page 1 of 1
No of Pages:	Page 1 of 1
Document Ref:	WBP-LAFT 01