This Business System has been produced by RAAS (UK) Ltd and must not be used in whole or in part without the express prior permission of © RAAS (UK) Ltd 2010



ANNUAL EXCAVATOR SLI CHECK SHEET

DATA LOGGER DOWNLOADED	HEIGHT LIMIT	SLEW LIMIT	SMALL WEIGHT	LARGE WEIGHT	Min. Rapius	Mid. Radius	Max. Radius		ENGINEER: S. WA	MAKE/MODEL: CASE 988
YES (TICK)	Boom:	LEFT:			4.68m	5. 99m	6.9M	Displayed Radius	5 WACTERCS.	08%
	DIPPER:	MOTION CUT:			4.7 mg.	6.03m	p. 801 m	Measured Radius	SIGNATURE:	DATE OF INSPECTION:
DATA LOGGER RECORDING OK	ARTIC BOOM:	RIGHT:						Known Weight Screen Weight	Hrs.	NEXT INSPECTION:
YES (TICK)	MOTION CUT:	MOTION CUT:	PASS.	0 ASS	8458	SAS	Encis	ASLI Function Pass/Fail	FLEET NO: 82	13/26

- Record both the displayed radius and the actual taped measurement. Set at maximum radius of machine taken from the duty charts and then tape from the centre of the slew ring to the centre of the lifting hook.
- Repeat for the minimum chart radius plus a mid-point check and record as above.
- 0 9 8 7 9 5 4 3 2 2 If radius checks okay, proceed with steps 5-8. IF Not - DO NOT PROCEED but arrange corrective action.
 - Lift a known weight at the max. radius detailed in the charts for that weight.
 - Repeat this using a small known weight.
 - Check the results are within the calibration as specified by PROLEC.
 - Check slew left and right for operation of limitation and motion cuts in both directions.
 - Check excavator arm height limitation and motion cuts against machine acceptance certificate.
- REPORT NY FINDINGS WHICH REQUIRE FURTHER CLARIFICATION OR ATTENTION

Document Ref:	No of Pages:	Issue Date:	Issue No:
 WBP-LAFT 01	Page 1 of 1	Oct 2016	4.1