






This Business System has been produced by RAAS (UK) Ltd and must not be used in whole or in part without the express prior permission of © RAAS (UK) Ltd 2010

WILLIAM BRADSHAW

ANNUAL EXCAVATOR SLI CHECK SHEET

MAKE/MODEL:	Case 988	DATE OF INSPECTION:	8/4/26	NEXT INSPECTION:	8/4/26	FLEET NO:	81
ENGINEER:	S. WATKINS	SIGNATURE:	<i>[Signature]</i>				
	Displayed Radius	Measured Radius	Known Weight	Screen Weight	ASLI Function	Pass/Fail	
MAX. RADIUS	6.66m	6.96m				Pass	
MID. RADIUS	5.50m	5.64m				Pass	
MIN. RADIUS	4.25m	4.43m				Pass	
LARGE WEIGHT			1930kg	1900kg		Pass	
SMALL WEIGHT			1170kg	1160kg		Pass	
SLEW LIMIT	LEFT: 	MOTION CUT: <input checked="" type="checkbox"/>	RIGHT: 	MOTION CUT: <input checked="" type="checkbox"/>			
HEIGHT LIMIT	BOOM: 	DIPPER: 	ARTIC BOOM: 	MOTION CUT: <input checked="" type="checkbox"/>			
DATA LOGGER DOWNLOADED	YES (Tick)		DATA LOGGER RECORDING OK	YES (Tick)			

METHOD:

1. Set at maximum radius of machine taken from the duty charts and then tape from the centre of the slew ring to the centre of the lifting hook.
2. Record both the displayed radius and the actual taped measurement.
3. Repeat for the minimum chart radius plus a mid-point check and record as above.
4. If radius checks okay, proceed with steps 5 - 8. **IF NOT - DO NOT PROCEED** but arrange corrective action.
5. Lift a known weight at the max. radius detailed in the charts for that weight.
6. Repeat this using a small known weight.
7. Check the results are within the calibration as specified by PROLEC.
8. Check slew left and right for operation of limitation and motion cuts in both directions.
9. Check excavator arm height limitation and motion cuts against machine acceptance certificate.
10. **REPORT ANY FINDINGS WHICH REQUIRE FURTHER CLARIFICATION OR ATTENTION**

Issue No:	4.1
Issue Date:	Oct 2016
No of Pages:	Page 1 of 1
Document Ref:	WBP-LAFT 01